

SILVER SERIES™ DRILL ROD



ECONOMICALLY-PRICED. Silver Series drill rod is a strong-performing, lower-cost option backed by Vermeer.



THREADED IN THE U.S. Silver Series drill rod is threaded in the same U.S. state-of-the-art facility as Firestick® drill rod.



QUALITY. Each rod is inspected to strict Vermeer tolerances and includes a batch number on the thread for traceability.



STEERABILITY. Composed of S135 grade steel, Silver Series drill rod is a considerable option for projects in which steerability has a moderate impact to the success of the project.



VARIABLE ROD SIZES. Silver Series drill rod is available in four sizes: 1.66" (4.2 cm), 1.9" (4.8 cm), 2.06" (5.2 cm) and 2.375" (6 cm) for use on the D7x11 through the D24x40 S3 Navigator® HDD models, including all current and legacy models in-between.



BALANCED. Like Firestick drill rod, Silver Series drill rod is designed with a proven balance of column wall thickness and connection strength for high steering performance.

SILVER SERIES™ DRILL ROD



D7x11 – D10x15 S3

Length: 6' (1.8 m)

Model compatibility: D7x11, D7x11A, D7x11 Series II, D9x13, D9x13 S3, D10x15 S3 Navigator® HDDs

Rod diameter: 1.66" (4.2 cm)

Drill rod thread: #200

Wall thickness: .191" (.5 cm)

Joint inside diameter: .75" (1.9 cm)

Joint outside diameter: 1.88" (4.8 cm)

Bend radius: 175' (53.3 m)



D20x22 SERIES II – D23x30 S3

Length: 10' (3.1 m)

Model compatibility: D18x22, D20x22, D20x22 Series II, D20x22 S3, D23x30 S3, D24x26 Navigator® HDDs

Rod diameter: 2.06" (5.2 cm)

Drill rod thread: #400

Wall thickness: .26" (.66 cm)

Joint inside diameter: .875" (2.22 cm)

Joint outside diameter: 2.25" (5.72 cm)

Bend radius: 164' (50 m)



D16x20A – D20x22 S3

Length: 10' (3.1 m)

Model compatibility: D16x20, D16x20A, D16x20 Series II, D18x22, D20x22, D20x22 S3 Navigator® HDDs

Rod diameter: 1.9" (4.8 cm)

Drill rod thread: #250

Wall thickness: .191" (.5 cm)

Joint inside diameter: .75" (1.9 cm)

Joint outside diameter: 2.125" (5.4 cm)

Bend radius: 188' (57.3 m)



D23x30 S3 – D24x40 S3

Length: 10' (3.1 m)

Model compatibility: D23x30 S3, D24x40, D24x40A, D24x40 Series II, D24x40 S3 Navigator® HDDs

Rod diameter: 2.375" (6 cm)

Drill rod thread: #600

Wall Thickness: .254" (0.65 cm)

Joint inside diameter: .875" (2.22 cm)

Joint outside diameter: 2.625" (6.67 cm)

Bend radius: 186' (56.7 m)

Vermeer Corporation reserves the right to make changes in engineering, design and specifications; add improvements; or discontinue manufacturing at any time without notice or obligation. Equipment shown is for illustrative purposes only and may display optional accessories or components. Please contact your local Vermeer dealer for more information on machine specifications. Vermeer, the Vermeer logo, Equipped to Do More, Firestick, Silver Series and Navigator are trademarks of Vermeer Manufacturing Company in the U.S. and/or other countries.

© 2017 Vermeer Corporation. All Rights Reserved. Printed in the U.S.A. Please recycle.

